

Product Details & Test Results

EFDURABB (single sided banner)

- Description:** An outdoor high strength laminated frontlit banner vinyl suitable for a range of applications including billboard skins, banners & other general indoor / outdoor graphics. It's properly engineered non shrinkage formulation & flat surface facilities print quality, maintains flatness during welding and can be stitched or eyeleted easily. Prints well on a large range of solvent, Latex UV digital and screen printing systems.
- Denier:** 840 x 840
- Weight:** 440gsm
- Width Availability:** Std: 1370mm, 2040mm, 2500mm, 3200mm, 4440mm, 5000mm (Cutting Service Available)
- Length:** 1370mm – 2500mm = 50 lineal meters. 3200mm – 5000mm = 58 lineal meters. Other lengths available on request.

Item	Unit	Value	Test Method
Base Fabric	Denier	840DX840D	(High tenacity yarn) 100%PES
Construction	Weaving/inch	9x9	/
Weight of fabric	Gsm/m2	75±5	DIN53352 BS3424 Method5B
Weight of PVC	Gsm/m2	365±5	DIN53352 BS3424 Method5B
Total weight	Gsm/m2	440±10	DIN53352 BS3424 Method5A
Thickness	mm	0.35±0.02	DIN EN ISO 2286-3
Width	cm	Up to 510	/
Tensile Strength	N/5cm	Warp	1350
		Weft	1200
Tearing Strength	N	Warp	245
		Weft	185
Adhesion	N/5CM	60	DIN53357 BS3425 Method9B
Temperature Resistance		-20~70	DIN53357 BS3425 Method10
Lacquering	None		
Flammability	We can apply for: B1, B2, NFPA701, etc.		
LOW CADMIUM & HEAVY METALS	We can be applied for : Cadmium free (EN71-3) or Reach Compliance		
DECLARATION	Please choose products suitably according to relative provisions or industrial standards. Shann DPM bears the responsibility for the specified technical and performance data on this page only. Shann DPM is not responsible for any other liability. (The technical data on this page is calculated on average, and ±5% tolerance is acceptable.)		