

Technical Data Sheet



Physical Data

Product	Edge Media Promo1 Edge Flow (EMPROMO1EF)
Description	PVC (100μ) with solvent adhesive, 2PE liner with Edge Flow (air egress bubble free)
Material	White PVC
Finish	Gloss
Basic weight	160gsm/m ± 5%
Thickness(Face film)	100μ ± 10μ
Liner thickness	160gsm 2PE
Adhesive-pressure sensitive	Removable / Clear / Solvent
Adhesive thickness	24gsm ± 2gsm
Available roll sizes	1370mm x 50m / 1524mm x 50m
Core size	76mm
Durability	Up to 2 years outdoor

EMPROMO1EF

Physical & Chemical Property	standard	unit	specs.
Face film	GB/T6672-2001	micron	100
Liner	GB/T4669-1995	gsm	160
Dimensional Stability	FINAT-14	mm	max. 0.8mm
Tensile Strength		N/inch	>50
Elongation		percentage	>170%
Gloss	GB8807-88		>50
Adhesion Initial	FINAT FTM-1	N/m	400
Adhesion Ultimate	FINAT FTM-1	N/m	540
Tearing		MN	>1000
Release	FINAT - 4	g/inch	15 ~ 40
Flamability			Self Extinguishing
Shelf Life	Stored at 22°C	Months	12
Durability Unprinted	Vertical Exposure	Months	24
Application Temperature		°C	Minimum 3
Temperature Range		°C	-20 - 60

