

Technical Data Sheet



Physical Data

Product	Edge Media Promo1 Removable Blockout (EMPROMO1RB)
Description	PVC (100μ) with solvent adhesive (monomeric), 2PE liner
Material	White PVC
Finish	Gloss
Basic weight	160gsm/m ± 5%
Thickness(Face film)	100μ ± 10μ
Liner thickness	160gsm 2PE
Adhesive-pressure sensitive	Removable / Grey / Solvent
Adhesive thickness	24gsm ± 2gsm
Available roll sizes	1370mm x 50m / 1524mm x 50m
Core size	76mm
Durability	Up to 2 years outdoor

EMPROMO1RB

Physical & Chemical Property	standard	unit	specs.
Face film	GB/T6672-2001	micron	100
Liner	GB/T4669-1995	gsm	160
Dimensional Stability	FINAT-14	mm	max. 0.8mm
Tensile Strength		N/inch	>50
Elongation		percentage	>170%
Gloss	GB8807-88		>50
Adhesion Initial	FINAT FTM-1	N/m	400
Adhesion Ultimate	FINAT FTM-1	N/m	540
Tearing		MN	>1000
Release	FINAT - 4	g/inch	15 ~ 40
Flamability			Self Extinguishing
Shelf Life	Stored at 22°C	Months	12
Durability Unprinted	Vertical Exposure	Months	24
Application Temperature		°C	Minimum 3
Temperature Range		°C	-20 - 60

