

Product Details & Test Results
Eclipse Blockout

100% warp-knitted polyester fabric with a white face and black resin coated backing. The slight stretch in both directions makes it an ideal solution in frame and exhibition displays while still offering full opacity.

Printability: UV, Latex, Sublimation direct and Sub paper transfer

Features: PVC free, Phthalate free, full opacity and slight stretch

Item	Metric	Imperial	Test Method
Total Weight	270 g/sqm	7.9 oz/sqyd	DIN EN ISO 2286-2, ASTM D751
Base Fabric	100% Polyester		DIN 60001, ASTM D7641
Weave Method	Warp-knitted		-
Shrinkage	≤ 3%		210°C, 30s
Light Transmittance	100%		ANSI PH2.19, ISO 5/2
Flame Resistance	Pass		DIN 4102-1-B1, NFPA 701 Test 1, EN13501-1
Recommended Fixation Temperature	190°C - 210°C, 1 - 2min		-
Yellowing Temperature	≥ 210°C		SUPRKC REX-C400, 30s
Width Available	Max 320cm	126"	DIN EN ISO 3759, ASTM D751-2006
Standard Length	50m	55 yds	DIN EN ISO 3759, ASTM D751-2006

ECLIPSE



All our technical characteristics are indicative

www.shannrpm.com