

**Product Details & Test Results**  
Flag

100% polyester warp-knitted textured fabric with semi-matte surface. Minimal shrinkage and a strong construction, making it ideal for all flag applications.

**Printability:** Sublimation direct and Sub paper transfer

**Features:** PVC free, Phthalate free and excellent ink penetration

Item	Metric	Imperial	Test Method
<b>Total Weight</b>	110 g/sqm	3.2 oz/sqyd	DIN EN ISO 2286-2, ASTM D751
<b>Base Fabric</b>	100% Polyester		DIN 60001, ASTM D7641
<b>Weave Method</b>	Warp-knitted		-
<b>Shrinkage</b>	≤ 2%		210°C, 30s
<b>Flame Resistance</b>	Pass		DIN 4102-1-B1, NFPA 701 Test 1, EN13501-1
<b>Recommended Fixation Temperature</b>	190°C - 210°C, 1 - 2min		-
<b>Yellowing Temperature</b>	≥ 210°C		SUPRKC REX-C400, 30s
<b>Width Available</b>	Max 320cm	126"	DIN EN ISO 3759, ASTM D751-2006
<b>Standard Length</b>	100m	110 yds	DIN EN ISO 3759, ASTM D751-2006

FLAG



All our technical characteristics are indicative

[www.shannrpm.com](http://www.shannrpm.com)