

**Product Details & Test Results**  
Podium Floor Covering

Printable floor covering textile offering good durability, exceptional flatness properties and dimensional stability, as well as slip resistance and fire retardancy.

- Printability:** UV and Latex
- Cutting:** Digital cutting systems, Stanley knife
- Features:** B1 FR, CSIRO P3 slip rated, can be clear coated to add durability to prints, contact your Shann team member for more details
- Applications:** Indoor promotional and decorative floor graphics for events, retail, exhibitions and activations

| Item                        | Value                              | Test Method               |
|-----------------------------|------------------------------------|---------------------------|
| <b>Fabric</b>               | High tenacity yarns<br>100% PES    | DIN EN ISO2060            |
| <b>Construction</b>         | 1000x1000 Denier                   | DIN60001                  |
| <b>Total weight</b>         | 1000g/sq.m                         | DIN53352 BS3424 method5A  |
| <b>Tensile strength</b>     | Warp: 2100N/5cm<br>Weft: 1800N/5cm | DIN53354 BS3424 method6A  |
| <b>Tearing strength</b>     | Warp: 230N<br>Weft: 185N           | DIN53356 BS3424 method 7A |
| <b>Adhesion</b>             | 60N/5cm                            | DIN53357 BS3425 method9B  |
| <b>Suitable temperature</b> | -20 - +70°C                        | DIN 53372 BS3424 method10 |
| <b>Flame retardancy</b>     | Pass                               | DIN 4102 B1               |

PODIUM

All our technical characteristics are indicative

[www.shannrpm.com](http://www.shannrpm.com)