

Technical Datasheet EDGE FLEX Pre Hemmed Mesh 9x9

Product Description

Digital printing banner mesh in 9x9 construction with UV resistant formulation. 40mm reinforced hem on both sides to allow for eyeleting without further finishing.

Technical Data

Specifications		Testing Method
Width	160 /180 cm	
Roll Size	110m (other lengths available on request)	
Printability	Solvent, Eco Solvent, Latex & UV	
Flammability	Can be produced to B1 & NFPA701	
Solar Transmission	50%	
Base Fabric	100% PES, 1000 x 1000D 9x9, Knitted	DIN EN ISO 2060
Weight	200 g/m2 5.89 OZ/YDZ	DIN EN ISO 2286-2 BS 3424 Method 5A
Thickness	0.35mm	
Composition Fabric	90 g/m2 2.65 OZ/YDZ	DIN EN ISO 2286-2 BS 3424 Method 5B
Composition PVC	110 g/m2 3.24 OZ/YDZ	
Breaking Strength Warp	1000 N/Scm 225 LBS/2inch	DIN 53 354 BS 3424 Method 6A FS 5100
Breaking Strength Weft	1000 N/Scm 225 LBS/2inch	
Tear Strength Weft	200 N 45 LBS	DIN 53 363 BS 3424 Method FS 5134
Tear Strength Weft	200 N 45 LBS	
Adhesion Strength Weft	45 N 10 LBS	DIN 53 357 BS 3424 Method 9B FS 5970
Adhesion Strength Weft	45 N 10 LBS	

Notice: The purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All published documents are based on our R & D departments careful research and test work.