

Product Details & Test Results
RPET Display

100% polyester warp knitted fabric made from recycled yarns. The tight structure offers excellent resistance to wrinkling and minimal shrinkage making it ideal for displays, banners, seg and backdrop applications.

- Printability:** Latex, Sublimation direct and Sub paper transfer
Features: PVC free, Phthalate free, anti-wrinkle and tight structure
Treatment: FR (B1 certified)

Item	Metric	Imperial	Test Method
Total Weight	220 g/sqm	6.4 oz/sqyd	DIN EN ISO 2286-2, ASTM D751
Base Fabric	100% Recycled Yarns		DIN 60001, ASTM D7641
Weave Method	Warp-knitted		-
Shrinkage	≤ 2%		210°C, 30s
Light Transmittance	(56±4)%		ANSI PH2.19, ISO 5/2
Flame Resistance	Pass		DIN 4102-1-B1, NFPA 701 Test 1, EN13501-1
Recommended Fixation Temperature	190°C - 210°C, 1 - 2min		-
Yellowing Temperature	≥ 210°C		SUPRKC REX-C400, 30s
Width Available	Max 320cm	126"	DIN EN ISO 3759, ASTM D751-2006
Standard Length	50m	55 yds	DIN EN ISO 3759, ASTM D751-2006

DISPLAY



All our technical characteristics are indicative

www.shannrpm.com