

## **DIGITAL PRINT MEDIA**

## **EDGE TEX SPECIFICATION SHEET**

## Product Details & Test Results Stretch

Satin white 100% warp-knitted polyester fabric offering even stretch in both warp and weft making it ideal for tube and frame displays, geometric shapes and exhibition displays. This fabric is lightweight but still offers good opacity, wrinkle resistance and is pre heat treated to ensure minimal shrinkage in the heat press.

**Printability:** Sublimation Direct, Sublimation Paper Transfer and Latex

**Features:** PVC free, Phthalate free, B1 FR, even stretch in both directions, lightweight,

good opacity, wrinkle resistance and pre heat treated.

Item	Metric	Imperial	Test Method
Total Weight	230 g/sqm	6.8 oz/sqyd	DIN EN ISO 2286-2, ASTM D751
Base Fabric	Polyester		DIN 60001, ASTM D7641
Weave Method	Warp-knitted 2 bar		-
Shrinkage	≤ 2%		210°C, 30s
Shielding Rate	63%		ANSI PH2.19, ISO 5/2
Flame Resistance	Pass		DIN 4102-1-B1, NFPA 701 Test1
Recommended Fixation Temperature	190°C, 30s		-
Elasticity	Warp: 10%, Weft: 10%		Length*Width: 200*50mm, Speed: 100mm/min, Tension: 20N
Width Available	Max 320cm	126"	DIN EN ISO 3759, ASTM D751-2006
Standard Length	50m	55 yds	DIN EN ISO 3759, ASTM D751-2006



All our technical characteristics are indicative

www.shanndpm.com

