

WALL GRAPHICS®

REMOVABLE
WALL FILMS



Nekoosa's Wall Graphics® portfolio is a comprehensive offering of repositionable, easily removable films for interior and exterior wall graphic applications.

Wall Graphics

Microsphere Removable Adhesive	High-Peel Removable Adhesive
<ul style="list-style-type: none"> • Matte white or gloss white finishes • 4, 6 and 8 mil facestock rated for <3 years of outdoor use • Augusta Wall Graphics® 6 mil semi-rigid textured embossed with 90# layflat polycoated paper liner also available • Suitable for short term indoor and outdoor applications (<1 year clean removability from application surfaces) • Recommended application surfaces: smooth, flat painted walls, wall paper, wood paneling, concrete, polished stone, stainless steel, glass 	<ul style="list-style-type: none"> • High-peel adhesive properties allow for a broader range of application surfaces – painted plywood, textured walls and low-to-no VOC paints • 6 mil semi-rigid matte white facestock rated for <3 years of outdoor use • Options available with a 90# layflat or 90# air-egress layflat polycoated paper liner • Suitable for indoor and outdoor applications (<6 months clean removability from application surfaces) • Recommended application surfaces: painted plywood, textured walls, sheetrock, concrete and cinder block

High opacity films with an excellent white point

Stable 90# layflat polycoated paper liner for ease of printing and installation

Print Compatibility: Wide Format (Solvent, Eco-Solvent, Latex and UV), Offset (Conventional and UV), HP Indigo and Screen

NEW PVC-FREE  **Wall Graphics® Matte White:** 4 mil, matte white film designed with a 90# layflat release liner and microsphere removable adhesive. Enhanced topcoat for Latex and UV wide format printing with outdoor durability up to 4 years.



This logo represents Nekoosa's commitment to offering sustainable alternatives to traditional PVC materials. We're happy to offer a PVC-Free option in this product line.

Applications

Interior and Exterior Wall Graphics

Wall Décor

Point-of-Purchase Wall Signage

Renovation Barricades

Wayward Signage

Posters

Textured Wall Graphics

Certified for
HP Latex Inks

Certified for
HP Indigo



WALL GRAPHICS® | REMOVABLE WALL FILMS



STOCKED PRODUCTS ▶

	Finish/Color	SKU #	Size	Thickness	Adhesive	Liner	Rolls/Carton
Wide Format							
	Matte White	SPMWGW5450	54" x 50 yd	4 mil	Microsphere Removable	90# Layflat	1
	Matte White	SPMWGW6050	60" x 50 yd	4 mil	Microsphere Removable	90# Layflat	1
NEW	Matte White	SPMWG5450PP	54" x 50 yd	4 mil	Microsphere Removable	90# Layflat	1
	Gloss White	SPMWG6G5450	54" x 50 yd	6 mil	Microsphere Removable	90# Layflat	1
	Augusta Embossed Matte White	SPMAUG5450	54" x 50 yd	6 mil	Microsphere Removable	90# Layflat	1
	Matte White	SPMWG65450	54" x 50 yd	6 mil	Microsphere Removable	90# Layflat	1
	Matte White	SPMWG66050	60" x 50 yd	6 mil	Microsphere Removable	90# Layflat	1
	Matte White	SPM600FW/R5450	54" x 50 yd	6 mil	High-Peel Removable	90# Layflat	1
	Matte White	SPE600FW/R5450	54" x 50 yd	6 mil	High-Peel Removable	90# Layflat Air-Egress	1
	Matte White	SPMWG85450	54" x 50 yd	8 mil	Microsphere Removable	90# Layflat	1


	Finish/Color	SKU #	Size	Thickness	Adhesive	Liner	M Wgt	Sheets/Carton
HP Indigo								
	Matte White	SPMWG6IN1218	12" x 18"	6 mil	Microsphere Removable	90# Layflat	116.7	300
	Matte White	SPMWG6IN1319	13" x 19"	6 mil	Microsphere Removable	90# Layflat	133.3	300

= PVC-Free

NEKOOSA BUCKS available in select rolls listed above.

Easy to apply and remove from these surfaces:

Microsphere Removable



High-Peel Removable



CUSTOM SIZE OFFERING ▶

Finish/Color	SKU #	Size (width)	Film Thickness	Adhesive	Liner	Wgt/MSI
Non Top Coated - UV Offset, Screen						
Matte White	WG400W	54"/60"	4 mil	Microsphere Removable	90# Layflat	.50#
Augusta Embossed Matte White	AUGUSTA	54"/60"	6 mil	Microsphere Removable	90# Layflat	.62#
Matte White	WG600W	54"/60"	6 mil	Microsphere Removable	90# Layflat	.62#
Matte White	CV600FW/R	54"/60"	6 mil	High-Peel Removable	90# Layflat	.62#
Matte White	CV600FWR/AE	54"/60"	6 mil	High-Peel Removable	90# Layflat Air-Egress	.62#
Matte White	WG800W	54"	8 mil	Microsphere Removable	90# Layflat	.70#

Finish/Color	SKU #	Size (width)	Film Thickness	Adhesive	Liner	Wgt/MSI
Top Coated - Conventional Offset, Water Based Flexo						
Matte White	WG400W/TC	54"/60"	4 mil	Microsphere Removable	90# Layflat	.50#
Matte White	WG600W/TC	54"/60"	6 mil	Microsphere Removable	90# Layflat	.62#
Matte White	WG400W/PP	54"	4 mil	Microsphere Removable	90# Layflat	.38#

Custom Size Offering: Custom converted sheet and roll options available to meet your specific requirements.

 = PVC-Free



NEKOOSA BUCKS

available in select rolls listed above.

Certified for
HP Latex Inks

Certified for
HP Indigo

TECHNICAL DATA ▶

Conditions for Use		
Shelf Life		1 year
Clean Removability	W79	Up to 1 year
	R45	Up to 6 months
Outdoor Durability		Up to 3 years
Min Application Temp		40° F (4° C)
Service Temp Range		-20° to 150° F (-29° to 66° C)
Solvent Resistance		Good*
Water Resistance		Excellent

CPSIA Compliant

*Good for most petroleum solvents and lower aliphatic alcohols.
For ultimate solvent resistance, edge sealing is recommended.

Additional Information:

- Augusta Wall Graphics® is not suitable for overlaminates.
- For installation instructions, visit our website.

Wide Format

Physical Properties	SPMWGW	SPMWG6G	SPMAUG	SPMWGPP
Finish	Matte	Gloss	Embossed Matte	Matte
Color	White	White	White	White
Adhesive	Microsphere Removable - W79	Microsphere Removable - W79	Microsphere Removable - W79	Microsphere Removable - W79
Film	Calendered Vinyl	Calendered Vinyl	Calendered Vinyl	Polypropylene
Liner	90# Layflat	90# Layflat	90# Layflat	90# Layflat
Opacity	92% Minimum	95% Minimum	95% Minimum	85% Minimum
Gloss Level	8% Typical	90% Typical	2% Typical	8% Typical
Thickness	Film	3.2 ± 0.2 mil	5.5 ± 0.2 mil	6 ± 0.2 mil
	Film w/ Adhesive	3.9 ± 0.2 mil	6.5 ± 0.2 mil	6.7 ± 0.2 mil
	Total Thickness	10.5 ± 0.4 mil	13.0 ± 0.4 mil	13.2 ± 0.4 mil
Adhesion	SS 15 min Room Temp Dwell	16-20 oz/in	16 - 20 oz/in	10-15 oz/in
	SS 24 hr Room Temp Dwell	23-27 oz/in	23- 27 oz/in	23-27 oz/in
Weight	Film w/ Adhesive	130-135 gsm	210-215 gsm	265-270 gsm
	Total w/ Liner	280-290 gsm	360-365 gsm	410-420 gsm
Printability	Latex, UV Inkjet, Eco-Solvent, Solvent	Latex, UV Inkjet, Eco-Solvent, Solvent	Latex, UV Inkjet, Eco-Solvent, Solvent	Latex, UV Inkjet
Fire Rating	ASTM E84 Class 1 or A	ASTM E84 Class 1 or A	ASTM E84 Class 1 or A	-

	SPMWG6	SPM600FW/R	SPE600FW/R	SPMWG8
Finish	Matte	Matte	Matte	Matte
Color	White	White	White	White
Adhesive	Microsphere Removable - W79	High-Peel Removable - R45	High-Peel Removable - R45	Microsphere Removable - W79
Film	Calendered Vinyl	Calendered Vinyl	Calendered Vinyl	Calendered Vinyl
Liner	90# Layflat	90# Layflat	90# Layflat w/ Air-Egress	90# Layflat
Opacity	95% Minimum	95% Minimum	95% Minimum	97% Minimum
Gloss Level	8% Typical	10% Typical	10% Typical	8% Typical
Thickness	Film	5.5 ± 0.2 mil	5.5 ± 0.2 mil	5.5 ± 0.2 mil
	Film w/ Adhesive	6.2 ± 0.2 mil	6.5 ± 0.2 mil	7.5 ± 0.2 mil
	Total Thickness	12.5 ± 0.4 mil	13.0 ± 0.4 mil	13.5 ± 0.4 mil
Adhesion	SS 15 min Room Temp Dwell	16-20 oz/in	33 - 37 oz/in	23-27oz/in
	SS 24 hr Room Temp Dwell	23-27 oz/in	48 - 52 oz/in	43-47 oz/in
Weight	Film w/ Adhesive	215-220 gsm	220-225 gsm	220-225 gsm
	Total w/ Liner	355-365 gsm	370-375 gsm	380-385 gsm
Printability	Latex, UV Inkjet, Eco-Solvent, Solvent	Latex, UV Inkjet, Eco-Solvent, Solvent	Latex, UV Inkjet, Eco-Solvent, Solvent	Latex, UV Inkjet, Eco-Solvent, Solvent
Fire Rating	ASTM E84 Class 1 or A	ASTM E84 Class 1 or A	ASTM E84 Class 1 or A	-

HP Indigo

Physical Properties	SPMWG6IN	
Finish	Matte	
Color	White	
Adhesive	Microsphere Removable - W79	
Film	Calendered Vinyl	
Liner	90# Layflat	
Opacity	95% Minimum	
Gloss Level	8% Typical	
Thickness	Film	5.5 ± 0.2 mil
	Film w/ Adhesive	6.2 ± 0.2 mil
	Total Thickness	12.5 ± 0.4 mil
Adhesion	SS 15 min Room Temp Dwell	16-20 oz/in
	SS 24 hr Room Temp Dwell	23-27 oz/in
Weight	Film w/ Adhesive	215-220 gsm
	Total w/ Liner	360-370 gsm
Printability	HP Indigo	
Fire Rating	ASTM E84 Class 1 or A	

UV Offset, Screen

		WG400W	AUGUSTA	WG600W	CV600FW/R
Physical Properties - Non Top Coated					
Finish		Matte	Embossed Matte	Matte	Matte
Color		White	White	White	White
Adhesive		Microsphere Removable - W79	Microsphere Removable - W79	Microsphere Removable - W79	High-Peel Removable
Film		Calendered Vinyl	Calendered Vinyl	Calendered Vinyl	Calendered Vinyl
Liner		90# Layflat	90# Layflat	90# Layflat	90# Layflat
Opacity		92% Minimum	95% Minimum	95% Minimum	95% Minimum
Gloss Level		8% Typical	2% Typical	8% Typical	10% Typical
Thickness	Film	3.2 ± 0.2 mil	6 ± 0.2 mil	5.5 ± 0.2 mil	5.5 ± 0.2 mil
	Film w/ Adhesive	3.9 ± 0.2 mil	6.7 ± 0.2 mil	6.2 ± 0.2 mil	6.5 ± 0.2 mil
	Total Thickness	10.5 ± 0.4 mil	13.2 ± 0.4 mil	12.5 ± 0.4 mil	13.0 ± 0.4 mil
Adhesion	SS 15 min Room Temp Dwell	16-20 oz/in	16-20 oz/in	16-20 oz/in	33-37 oz/in
	SS 24 hr Room Temp Dwell	23-27 oz/in	23-27 oz/in	23-27 oz/in	48-52 oz/in
Weight	Film w/ Adhesive	130-135 gsm	265-270 gsm	215-220 gsm	220-225 gsm
	Total w/ Liner	280-290 gsm	410-420 gsm	355-365 gsm	370-375 gsm
Printability		Offset, Screen	Offset, Screen	Offset, Screen	Offset, Screen
Fire Rating		ASTM E84 Class 1 or A	ASTM E84 Class 1 or A	ASTM E84 Class 1 or A	ASTM E84 Class 1 or A

		CV600FWR/AE	SPMWGPP	WG800W
Finish		Matte	Matte	Matte
Color		White	White	White
Adhesive		High-Peel Removable - R45	Microsphere Removable - W79	Microsphere Removable - W79
Film		Calendered Vinyl	Polypropylene	Calendered Vinyl
Liner		90# Layflat w/ Air-Egress	90# Layflat	90# Layflat
Opacity		95% Minimum	85% Minimum	97% Minimum
Gloss Level		10% Typical	8% Typical	8% Typical
Thickness	Film	5.5 ± 0.2 mil	3.6 ± 0.2 mil	6.5 ± 0.2 mil
	Film w/ Adhesive	7.5 ± 0.2 mil	4.3 ± 0.2 mil	7.2 ± 0.2 mil
	Total Thickness	13.5 ± 0.4 mil	10.8 ± 0.5 mil	13.5 ± 0.4 mil
Adhesion	SS 15 min Room Temp Dwell	23-27oz/in	10-15 oz/in	16-20 oz/in
	SS 24 hr Room Temp Dwell	43-47 oz/in	13-17 oz/in	23-27 oz/in
Weight	Film w/ Adhesive	220-225 gsm	105-115 gsm	245-250 gsm
	Total w/ Liner	380-385 gsm	220-260 gsm	400-410 gsm
Printability		Offset, Screen	Offset, Screen	Offset, Screen
Fire Rating		ASTM E84 Class 1 or A	-	-

Conventional Offset, Water Based Flexo

		WG400W/TC	WG600W/TC
Physical Properties – Top Coated			
Finish		Matte	Matte
Color		White	White
Adhesive		Microsphere Removable - W79	Microsphere Removable - W79
Film		Calendered Vinyl	Calendered Vinyl
Liner		90# Layflat	90# Layflat
Opacity		92% Minimum	95% Minimum
Gloss Level		8% Typical	8% Typical
Thickness	Film	3.2 ± 0.2 mil	5.5 ± 0.2 mil
	Film w/ Adhesive	3.9 ± 0.2 mil	6.2 ± 0.2 mil
	Total Thickness	10.5 ± 0.4 mil	12.5 ± 0.4 mil
Adhesion	SS 15 min Room Temp Dwell	16-20 oz/in	16-20 oz/in
	SS 24 hr Room Temp Dwell	23-27 oz/in	23-27 oz/in
Weight	Film w/ Adhesive	130-135 gsm	215-220 gsm
	Total w/ Liner	280-290 gsm	355-365 gsm
Printability		Conventional Offset & Water-Based Flexo	Conventional Offset & Water-Based Flexo
Fire Rating		ASTM E84 Class 1 or A	ASTM E84 Class 1 or A

The information provided herein is correct to the best of Nekoosa's knowledge, however, should not be construed as specifications. No liability for any errors, facts or opinions are accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

