DIGI - PANE

Introduction

Digi-Panel is a quality range of Aluminium Composite Panel that comes in various specifications. All sheets are manufactured with an optimized special PE coating designed specifically for superior ink adhesion when printed with UV Cured ink – testing is advised. Digi-Panel Premium has a 0.30mm thick Aluminium skin that can be routed one side then bent into desired shapes to suit 2D & 3D applications, Digi-Panel Sign with a 0.21mm Aluminium skin is a perfect all round product for flat indoor & outdoor signage and Digi-Panel Lite with a 0.15mm Aluminium skin is a perfect economical product where cost saving is required. Available in a full range of sizes, thicknesses and finishes Australia wide Digi-Panel is an ideal product to have on hand for every industrial print house and sign manufacturer.





Product Range

All Digi-Panel products have an optimised polyester coating, designed specifically for UV cured printing.















DIGI - PANEL

SIGN

- Signage grade
- 0.21mm Aluminium skin
- UV cured printable
- Available in wide range of sizes
- **UV** resistant

Available Nationally





- Melbourne
- Sydney
- Brisbane
- Perth
- Adelaide
- Darwin


DIGI - PANEL


Finishing Techniques




















Info


Digi-Panel is an extremely versatile product that can be finished in many different ways to suit a vast range of applications. Whether your finished application is 2D or 3D, there is a Digi-Panel product right for the job.






Digi-Panel Sign is just right for your standard finishing techniques such as drilling, sawing and riveting.

Please refer to the various diagrams of techniques on this page relevant to finishing the Digi-Panel product.





■ Diagrams are a guide only. Testing is recommended.

DIGI - PANEL

Product Specifications

Shann Australia | Digi-Panel Specification testing

| Dimensional tolerances | Test | Test value | |
|--------------------------------|---|---|--|
| Length (mm) | ±2mm | 1mm | |
| Width (mm) | ±2mm | 0mm | |
| Thickness (mm) | ±0.2mm | -0.04mm – +0.02mm | |
| Squareness (mm) | ≤5mm | 1mm | |
| Edge Straightness (mm) | ≤1mm/m | 0.2mm/m | |
| Warp Resistance | ≤5mm/m | 5.0mm/m | |
| Surface properties | Test | Test value | |
| Coating Thickness | Min. >16 micron | Average 28 micron | |
| Gloss Tolerance | <10 | 2.2 | |
| Pencil Hardness | >HB | 2H | |
| Coating Flexibility | <3T | ОТ | |
| Coating Adhesive | Not Lower than class 1 | Class 0 | |
| Impact Resistance | 50Kg – CM / No Crack | 50Kg – CM / No Crack | |
| Boiling Water Resistance | Boil for 2 Hours without change | No Change | |
| Acid Resistance | Immerse surface in 20% HC1 for 24 hours without change | No Change | |
| Alkaline Resistance | Immerse surface in 20% NaOH for 24 hours without change | No Change | |
| Oil Resistance | Immerse surface in 20% engine oil for 24 hours without change | No Change | |
| Solvent Resistance | Wipe 100 times with solvent without change | No Change | |
| Scrub Resistance | >10 000 times without Change | No Change | |
| Physical properties | Test | Test value | |
| Bending Strength | >60mPa | 78MPa | |
| Bending elastic modulus | >1.5 x 104 Mpa | 2.1 x 104 MPa | |
| Penetration resistance | >5.0kN | 5.0kN | |
| Shearing Strength | >20.0MPa | 21.3MPa | |
| 180º Peel Strength | >5.0 Newton /.mm | 6.5 Newton / mm | |
| Thermal Expansion Coefficient | <4.00 x 10 ⁻ 5 °C | 1.27 x 10 ⁻ 5 ^o C ⁻¹ | |
| Heat Distortion Temperature | >95 ºC | 106 ºC | |
| Properties | Test | | |
| Standard panel sizes in mm | 1220 x 2440 1220 x 3050 1220 x 3660 1220 x 4000 1500 x 3050 1500 x 3660 (other sizes available by request - subject to MOQ) | | |
| Aluminium skin thickness in mm | 0.15 0.21 0.30 Aluminium Alloy 3000 series | | |
| Panel thickness in mm | 2 3 4 | | |
| Weight Kg per square metre | Digi-Panel Premium 4.56 Digi-Panel Sign 4.26 Digi-Panel Lite 4.08 | | |
| Warranty Details | | | |

Warranty Details

| Warranty | Satin PE Surface | Gloss Surface | De-lamination |
|--------------------|---------------------------------|---------------------------------|---------------------------------|
| Digi Panel Premium | 10 year indoor / 5 year outdoor | 10 year indoor / 3 year outdoor | 10 year indoor / 5 year outdoor |
| Digi Panel Sign | 10 year indoor / 5 year outdoor | 10 year indoor / 3 year outdoor | 10 year indoor / 5 year outdoor |
| Digi Panel Lite | 10 year indoor / 5 year outdoor | 10 year indoor / 3 year outdoor | 10 year indoor / 5 year outdoor |