



TexPrint[®]UT

Utility Textile Grade

Easy-to-work-with, TexPrint[®]UT paper features economical ink usage, highest color yields and powerful economics in cost conscious, high-volume textile printing environments. TexPrint[®]UT papers are not designed for hard, smooth, or non-porous substrates.

FEATURES AND BENEFITS:

Largest selection of weights, widths and roll lengths

Get exactly the right size for your print environment with less waste, fewer roll changes and more up-time.

Flatness

TexPrint[®]UT lays flat. Prints flat. Resists cockling even under heavy ink loads. No head strikes, no worries.

Fast ink absorption

Easily keeps pace with the fastest commercial textile printers without offsetting.

Faster transfers

UT allows heat to migrate through the print sheet quicker, allowing lower calender dwell times and faster transfer speeds.

High color yield

More color from less ink. More color on your fabric, less ink left on the transfer paper.

APPLICATIONS:

- > Banners
- > Blinds
- > Fashion Textiles
- > Home Décor
- > Soft Signage
- > Textiles
- > Trade Show Exhibits



TexPrint®UT Properties

	TexPrint®UT/58	TexPrint®UT/72	TexPrint®UT/92-Elite
Basis Weight	58 gsm	72 gsm	92 gsm
Thickness	75 µm	88 µm	109 µm
Core I.D.	76 mm / 3"	76 mm / 3"	76 mm / 3"
Standard Widths			
24" / 61.0 cm			•
36" / 91.4 cm		•	•
44" / 111.8 cm	•	•	•
54" / 137.2 cm	•	•	
64" / 162.0 cm	•	•	•
75" / 190.0 cm	•	•	•
104" / 264.0 cm			•
126" / 320.0 cm	•	•	•

*Recommended printing
conditions: 23-25 °C, 45-55% humidity*

Beaver Paper

2420 Tech Center Parkway, Bldg. 140
Lawrenceville, GA 30043 USA

Contact Customer Service & Sales
+1 770-935-5080 x1
orders@beaverpaper.com
info@beaverpaper.com

Beaver Paper GmbH

Im Lossenfeld 19
77731 Willstätt, Germany

Contact Customer Service
info@beaverpaper.com
customerservices@beaverpaper.de